

SONEDAS

Downlight empotrable



23000102

23000103

4.000K 	30.000 H	50.000 CICLOS ON-OFF
 120°	Ø 225 MM	 DF >0,7
220-240V 50-60Hz	18W	1.980 LUMENS

6.500K 	30.000 H	50.000 CICLOS ON-OFF
 120°	Ø 225 MM	 DF >0,7
220-240V 50-60Hz	18W	1.980 LUMENS

RoHS

SONEDAS

Downlight empotrable



E

23000104

23000105

4.000K 	30.000 H	50.000 CICLOS ON-OFF
 120°	225 X 225 MM	 DF >0,7
220-240V 50-60Hz	18W	1.980 LUMENS

6.500K 	30.000 H	50.000 CICLOS ON-OFF
 120°	225 X 225 MM	 DF >0,7
220-240V 50-60Hz	18W	1.980 LUMENS

RoHS

SONEDAS

Downlight de superficie



E

23000106

23000107

4.000K 	30.000 H	50.000 CICLOS ON-OFF
	Ø 225 MM	
220-240V 50-60Hz	18W	1.980 LUMENS

6.500K 	30.000 H	50.000 CICLOS ON-OFF
	Ø 225 MM	
220-240V 50-60Hz	18W	1.980 LUMENS

RoHS

SONEDAS

Downlight de superficie



23000108

23000109

4.000K 	30.000 H	50.000 CICLOS ON-OFF
 120°	225 X 225 MM	 DF >0,7
220-240V 50-60Hz	18W	1.980 LUMENS

6.500K 	30.000 H	50.000 CICLOS ON-OFF
 120°	225 X 225 MM	 DF >0,7
220-240V 50-60Hz	18W	1.980 LUMENS