



05452/ 05454 / 05456 tesa® Moll® Foam Universal

Product Description/ Application: tesa Moll® Foam Universal

The classic self-adhesive foam draught excluder for windows and doors is easy to fit. Protects against cold, draughts, dust, noise and saves energy. Easy to adapt to different gap sizes due to flexible foam.

- Self-adhesive foam profile
- Seals gaps from 1 to 5 mm
- Durability of 2 years
- Soft and flexible
- Quick to remove
- Available in white
- Best to be applied at 10 °C – 20 °C
- Temperature-resistant from -20 °C to +60 °C

Dimensions:

Lengths / widths / thickness of profiles	05452:	10 m : 9 mm : 5 mm
	05454:	10 m : 15 mm : 5 mm
	05456:	10 m : 25 mm : 5 mm

Technical Data: (mean values)

Backing:	open cell PU foam on PP film	Total thickness:	6.2 +0.6/-0.4 mm
Color:	white	Adhesion/Steel:	4.8 ± 1.4 N/cm
Adhesive:	acrylic	Gap coverage:	1 – 5 mm
Liner:	glassine paper		

8320 – 04/10

tesa SE
P.O. Box 57 02 62
D-22771 Hamburg
Telephone +49-40-49 09 2618
Telefax +49-40-49 09 4621

tesa self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The Advisory Section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.