

05422

tesamoll® Door-to-floor Foam Tape

Product Description/ Application:

tesamoll® door-to-floor- foam

The self-adhesive general purpose foam draught excluder for doors is easy to apply on the bottom of every door. Protects against cold, draughts, dust and noise and saves energy. Recommended for even floors.

- Self-adhesive, long-lasting foam profile
- Seals gaps from 1 to 19 mm
- Durability to 2 years
- Soft and flexible
- Available in white and brown
- Best to be applied at 5°C-30°C
- Temperature-resistant from -20°C to +40°C

tesa SE

P.O. Box 57 02 62
D-22771 Hamburg
Telephone +49-40-49 09 5593
Telefax +49-40-49 09 18 5593

tesa self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The Advisory Section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.



tesa SE

Quality management

Internal page - Product information

Product name and -number: tesamoll® 05422 door-to-floor foam

Dimensions:

Colour	Lengths / widths / thickness of profiles
White or brown	1m: 38mm: 2mm

Technical Data: (mean values)

Backing:	PVC	Adhesion/ Steel	≥ 2,5 N/cm
Backing tape:	Non-woven		
Total thickness (without re-release liner):	2,32 +0,35/-0,25 mm	Gap coverage	1 – 19 mm
Adhesive:	Acrylate		

8320 – 02/08

tesa SE

P.O. Box 57 02 62

D-22771 Hamburg

Telephone +49-40-49 09 2618

Telefax +49-40-49 09 4621

A Beiersdorf Company

tesa self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The Advisory Section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.

Ident.no.:DoFB0006 Issue: 002 Valid from 03.01.1999