

05390 / 05395 / 05391 **tesamoll® Classic P-Profile**

Product Description/ Application:

- tesamoll® Classic P-Profile**
- The self-adhesive tesamoll® Classic P-Profile draught excluder for windows and doors is easy to fit and protects against draughts, cold, dust and noise, and therefore helps saving energy. Weather-resistant due to high quality rubber profile.
- Seals all gaps from 2mm to 5mm
 - Durability to 8 years
 - Weather-, UV- and ozone-resistant
 - Wipe-clean
 - Easy to fit without screws or nails
 - Easy to remove
 - Best to be applied at 5°C-25°C
 - Temperature-resistant from -50°C to +60°C



Quality
management

tesa SE

Product information

Product name and -number: PI P-profile 05390_05391_05395.doc

Dimensions:

Colour	Lengths / widths / thickness of profiles
White or Brown	05390: 6m: 9mm: 5,5mm 05395: 10m : 9mm: 5,5mm 05391: 25m : 9mm : 5,5mm

Technical Data: (mean values)

Backing:	Fabric	Adhesion/ Steel	$\geq 3,5 \text{ N / cm}$
Total thickness:	$5,7 \pm 0,5 \text{ mm}$	Gap coverage	2 mm – 5 mm
Adhesive:	Synthetic Rubber		

8320 – 02/06

tesa SE

Quickbornstr 24

D- 20253 Hamburg

Telephone +49-40-49 09 0

Telefax +49-40-49 09 18 5593

tesa self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The Advisory Section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.