

3

3M™ Universal Antislip Tape (black, yellow and black/yellow)**Technical Data Sheet****TD 804****Product description:**

The product consists of a Aluminumoxide particles bonded by a durable polymer to a flexible PVC film. The reverse side is coated with a pressure sensitive adhesive, covered by a removable protective paper liner. The product provides a durable, slip resistant surface for a large variety of applications.

Intended Use:

Primarily for use as a durable, slip resistant surface for dry, wet, oily floors in industrial and commercial applications with intensive pedestrian or light vehicle traffic

It designed to prevent slips at workplaces like ramps and heavy walk traffic corridors, fire escapes, ladders, stairs and in kitchens with wet oily floor areas.

Colour: black, yellow, yellow/black

Product Advantages:

- Safe, slip resistant surface
- Durable
- Easy to install
- good bond to most dry, clean, smooth surfaces

Sizes and Packaging

Rolls:		
Black		
25 mm x 20 m		24 rolls/box
50 mm x 20 m		12 rolls/box
100 mm x 20 m		12 rolls/box
150mm x 20 m		8 rolls/box
Yellow		
50 mm x 20 m		12 rolls/box
Black / Yellow		
50 mm x 20 m		12 rolls/box

Labeling:

Each box shall be labeled with product name, size, color and manufacturer's trade name.

Product Characteristics

Properties	Typical values
Total thickness	1,0 +/- 0,2mm
Paper liner	0,1 +/- 0,01mm
Adhesion to steel Afera 5001 / ISO 29862:2007	>15,0 N/25mm
Elongation at break Afera 5004 ISO 29864:2008	>25%
Application temperature	10°C to 40°C
Service temperature range	-5°C to 50°C
Resistance to water	good

Installation

Ensure that the surface is very clean and dry, having no dust, water or oil on it.

Please use rubber wheel and overroll by applying pressure on the 3M Antislip Tape.

Ensure to apply the Antislip Tape before 24 hrs to use.

Storage conditions:

- At RT / 65% RH



Important Notice to Purchaser / Converter / Wearer:

All statements, technical information and recommendations herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. We shall not be liable and no warranty shall apply for products not applied according to our published information folder.

Before using/converting, the user/converter must determine the suitability of the product for its intended use/converting, and the user/converter assumes all risk and liability whatsoever in connection therewith. All questions of warranty and liability relating to this product are governed by the terms of the sale subject where applicable to the prevailing law. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of us.

3Deutschland GmbH
Building & Commercial Services
D-41453 Neuss, Germany

DRAFT

